

**CELLOFOAM**<sup>®</sup>  
North America Inc.

# DOCK HARDWARE

## Galvanized Structural Steel

**Cellofoams' Dock Hardware** is designed for use with 1-1/2" thick lumber (minimum width 6"). All hardware is mounted with 1/2" carriage bolts. All male and female dock to dock connections are made with either 3/4" bolts with lock nuts or 3/4" connecting pins.



**Outside Corner (Female)** - has two 1/2" welded tabs. Use with a male out-side corner.  
Each leg is 10"L x 5"H.  
**RHH-OCF** WT 9.0lb



**Outside Corner (male)** - has one 1/2" welded tab. Use with a female outside corner to connect docks end to end. Joint requires 3/4" bolt set or connector pin (L).  
Each leg is 10"L x 5"H.  
**RHH-OCM** WT 8.5lb



**Outside Corner End** - use this corner at ends of fingers and docks. Ideal for swim floats and ski jump corners.  
Each leg is 10"L x 5"H.  
**RHH-OCE** WT 7.0lb



**Inside Corner** - this heavy-duty inside corner should be used with one of the outside corners. Each leg has elongated holes for easy fit-up and is 8-1/4"L x 6"H.  
**RHH-IC** WT 6.5lb



**Angle** - use this heavy-duty angle for all cross supports. Each leg is 2-1/2"L x 5"H.  
**RHH-A** WT 1.75lb



**Female T Connector** - has two welded 1/2" tabs. Bolts to side of dock to attach fingers and ramps. 5"L x 5"H.  
**RHH-SF** WT 3.5lb



**Male T Connector** - has one welded 1/2" tab. Use with female T connector to attach fingers and ramps. 5"L x 5"H. 3/4" bolt set required for joint.  
**RHH-SM** WT 3.25lb



**Washer Plate** - use two washer plates with each angle. Measures 1-1/2"L x 5"H.  
**RHHW** WT 0.5lb



**Chain Retainer** - bolts to side of dock. Use weights an chains to hold dock in place. Accommodates 1/4", 3/8", & 1/2" chain. 5"L x 5"H  
**RHCH** WT 3.75lb




**Connector Pin Set** - for quick disconnect. Used to connect male and female connectors. Galvanized 3/4" connector pin and hitch clip pin.  
**RHBPIN** WT 0.5lb



**Splice Plate** - used to securely add a finger to your dock or to strengthen a section of the dock beyond the length of the lumber. 25"L x 5"H WT 8.15lb



**Dock Cleats** - designed to bolt onto the decking surface so that boats and personal water crafts can be tied to the dock.  
**RHC8** 8"L WT 1.0lb  
**RHC10** 10"L WT 2.0lb




**Plate Backing** - designed for use with the single "T" to keep bolts from pulling through the wood. 4 slots for 3/8" hex head bolts ensure a secure hold; perfectly fits 1-1/2" thick lumber. 5"L x 5"H.  
**RHHB** WT 1.0lb



**Cleat Angle** - designed to accommodate various cleats and to help prevent the cleats from pulling out. Lightweight metal body ensures reliable use. 2.75"L x 2.75"H  
**RHHL-CA** WT 1.5lb



**Pipe Holder/Outside 3"** - bolt to out-side of dock. Carriage bolt set required for attaching. Use 2" pipe to hold dock in place.  
**RHP-3** WT 8.25lb



**Inside Corner/Pipe Holder 3"** - these heavy-duty inside corners should be used with one of the outside corners and has an internal pipe holder to be used with 2" pipe. Welded gusset gives strength to the dock's frame. 8-1/4"L x 5"H. Requires carriage bolt set for attaching.  
**RHH-O1C3** WT 11.5

**READILY ADAPTS TO ANY SIZE PERMAFLOAT<sup>®</sup> FLOAT DRUM!**

### CONYERS, GA

1961 Rockdale Industrial Blvd. 30012

### SALLISAW, OK

400 E. Houser Ave. 74955

*Our full line of float specifications are available online at*

**www.cellofoam.com**

*Please contact your Cellofoam PERMAFLOAT Dock Flotation Specialist for the most accurate assessment of your Dock Hardware needs. (800) 531-4734*